

# FENDT

## Implement Accessories





# For continued cutting edge, sophisticated performance in the field


Don't compromise your Fendt implement's performance. Ensure you only use Genuine Fendt replacement parts and accessory kits.

If the grass kits range highlighted does not include the part or application you are looking for, don't hesitate to contact your local dealer for more information.



# Drum mowers

## Cutter Accessories



### Cat. II triangular coupling frame

**FEL161748**

CUTTER 2940 FPV  
CUTTER 3140 FPV  
CUTTER 3340 FPV



### Swath deflector system

- Consisting of 2 rotating swath discs on the right + 2 on the left



**FEL42992409**

CUTTER 292  
CUTTER 310 TL



### Additional swath discs

Swath width ca.

- 0,65 - 1,00 m
- 0,65 - 1,20 m
- 0,85 - 1,40 m

**FEL42807609**

CUTTER 2940 FPV  
CUTTER 3140 FPV  
CUTTER 3340 FPV




### Telescopic upper linkage CAT. II, lockable

- adjustable distance: 500 - 700 mm / telescopic distance: 80 mm

**FEL141869**

CUTTER 2940 FPV  
CUTTER 3140 FPV  
CUTTER 3340 FPV




### Dividing disc

- For fitting on the feeder drums
- Better dividing of the forage on the outside

**FEL42989609**

SLICER cutterbar  
(compact angular gear)



### Gearbox 540 RPM

**FEL429920**

SLICER 3160 TLX  
SLICER 3160 TLXKC  
SLICER 3160 TLXRC



### Supports for parking with mower in vertical position

**FEL429908**

SLICER 3160 TLX/KC/RC  
SLICER 3670 TLX/KC/RC



### Spreader device for TLX/TL-V



**FEL429900**

SLICER 3160 TLXKC

**FEL429901**


SLICER 3670 TLXKC

**FEL429903**

SLICER3160 TLXRC

**FEL429904**

SLICER 3670 TLXRC




### Hydraulically folding end cover

**FEL429910**

SLICER 3160 TLX  
SLICER 3160 TLXKC  
SLICER 3160 TLXRC

**FEL492909**


SLICER 3670 TLX  
SLICER 3670 TLXKC  
SLICER 3670 TLXRC



#### Hydraulic transport locking system TLX/TL-V; additional SAV required

**FEL429914**

SLICER 3160 TLX/KC/RC  
SLICER 3670 TLX/KC/RC



#### Lighting set TLX/TL-V

**FEL429897**

SLICER 3160 TLX/KC/RC  
SLICER 3670 TLX/KC/RC




#### Additional skid

- For larger cutting heights: at least 2 pieces required for each cutter bar
- As wear protection for stony or sandy conditions  
(number of mower discs = number of additional anti-wear skids)

**FEL429918**


SLICER 3160 TLX/KC/RC  
SLICER 3670 TLX/KC/RC



### Electrical lightning and warning panels

**FEL17259009**

SLICER 3060 FP  
SLICER 3060 FPSL  
SLICER 3060 FPKC  
SLICER 3060 FPRC



### Electrical lightning and warning panels

**FEL17259109**

SLICER 310 FPK




### 1 welded-on skid

At least 3 necessary for each mower.

**FEL425927**

SLICER ISL



#### Protective cover

- For use without conditioner

**FEL42989304**

SLICER 3060 FPSL  
SLICER 3060 FPKC  
SLICER 3060 FPRC  
SLICER 310 FZKC  
SLICER 310 FZRC




#### Set of suppression hoops



**FEL42989509**

SLICER 310 FPK  
SLICER 3060 FP/SL/KC/RC  
SLICER 310 FZ/KC/RC






### Cat. II triangular coupling frame

**FEL161748**

SLICER 260 FP  
 SLICER 260 FPS  
 SLICER 310 FPK  
 SLICER 3060 FP  
 SLICER 3060 FPSL  
 SLICER 3060 FPKC  
 SLICER 3060 FPRC  
 SLICER 310 FZ  
 SLICER 310 FZKC  
 SLICER 310 FZRC



### Swath disc left


**FEL426238**

SLICER 270 P  
 SLICER 320 P



### 1 additional skid

- For larger cutting heights: at least 2 pieces (or 3 for working width larger 4,00 metre) required for each cutter bar
- As wear protection for stony or sandy conditions (number of mower discs = number of additional anti-wear skids)



**FEL42630609**

SLICER cutterbar  
 (compact angular gear)



#### Swath discs for operation without conditioner

\* 2x necessary

**FEL429891**

SLICER 3060 FP  
SLICER 310 FZ  
SLICER 911 TL\*  
SLICER 991 TL\*



#### Stone guard

\* 2x necessary

**FEL429890**

SLICER 3060 FPRC  
SLICER 310 FZRC  
SLICER 911 TLRC\*




### Mower disc with conveyor wings


**FEL429871**

SLICER cutterbar  
(compact angular gear)

NOT FOR:  
SLICER 260 FP  
SLICER 260 FPS




### Front mirror with holder



**FEL429892**

SLICER 310 FPK  
SLICER 3060 FP  
SLICER 3060 FPSL  
SLICER 3060 FPKC  
SLICER 3060 FPRC  
SLICER 310 FZ  
SLICER 310 FZKC  
SLICER 310 FZRC




#### Swath disc right

- 3,00 metre working width --> swath width approx.: 2,00 m
- 3,50 metre working width --> swath width approx.: 2,60 m
- 4,00 metre working width --> swath width approx.: 3,00 m
- 4,50 metre working width --> swath width approx.: 3,50 m

**FEL42799609**

SLICER 3060 TL  
SLICER 3570 TL  
SLICER 4080 TL  
SLICER 4590 TL





#### Hydraulic foldable protective covers

**FEL429919**

SLICER 3060 FP  
SLICER 3060 FPSL  
SLICER 3060 FPKC  
SLICER 3060 FPRC



	<b>Metal plate</b> <ul style="list-style-type: none"><li>• Installation between cutter bar and conveyor belt</li></ul>
<b>FEL429932</b>	SLICER 9314 TLKCB
<b>FEL429933</b>	SLICER 8312 TLKCB

	<b>Curved blade</b> <ul style="list-style-type: none"><li>• For stony conditions</li><li>• NOT FOR mowers with quick blade change</li></ul>
<b>FEL138867</b>	SLICER cutterbar (compact angular gear)



#### Night swath gear

Reduction of the rotor revs with same direction of rotation of the spinner for

- The depositing of small swaths instead of spreading the forage
- Less dew penetrating the forage overnight

**FEL48464609**

TWISTER 5204 DN  
TWISTER 6606 DN  
TWISTER 7706 DN  
TWISTER 901 T

**FEL15362409**

TWISTER 11008 T  
TWISTER 13010 T

**FEL48465009**

TWISTER 8608 DN



#### Electric lighting

**FEL152500**

TWISTER 431 DN  
TWISTER 601 DN




### Electric lighting

To be mounted on warning plates 715 735 0000 / FEL150434 only

**FEL15360709**

TWISTER 5204 DN  
TWISTER 6606 DN  
TWISTER 7706 DN  
TWISTER 8608 DN



### CH reflector set

**FEL150732**

TWISTER alpin-serie  
TWISTER rear 3-point linkage



#### Contact wheel (15/6.00-6)

- Optionally available spring-centred creeper wheel (upper link is in a hanging mounting link on the 3-point hitch)
- Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor

FEL48464701



TWISTER 5204 DN  
TWISTER 6606 DN  
TWISTER 7706 DN



#### Contact wheel (13/6.50-6)

- Optionally available spring-centred creeper wheel
- Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor
- Very small space between contact wheel and tines, i.e. optimal adjustment of the machine to the ground, even in the case of short-wave ground contours

FEL48464801



TWISTER 431 DN  
TWISTER 601 DN





### Attachment kit

- Required for installing the tedder on standard tractors
- Displacement of 115 mm to the rear

**FEL489731**

TWISTER 431 DN  
TWISTER 601 DN



### Contact wheel (16/6.50-8)

- Optionally available spring-centred creeper wheel (upper link is in a hanging mounting link on the 3-point hitch)
- Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor

**FEL48467401**



TWISTER 8608 DN



### 1 set of contact wheels (18.5/8.50-8)

- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor
- Very small space between contact wheel and tines, i.e. optimal adjustment of the machine to the ground, even in the case of short-wave ground contours

**FEL48467601**

TWISTER 901 T



#### Hydraulic edge spreading device

Additional 1x SAV necessary

Tilting of the machine using single-acting hydraulic cylinder

- Forage is not thrown onto adjacent areas
- Prevents the machine from drifting down extreme slopes



**FEL48467509**

TWISTER 5204 DN  
TWISTER 6606 DN  
TWISTER 7706 DN  
TWISTER 8608 DN



#### Tine-loss safety guard (1x)

Maximum protection for following harvesting machines, in order to prevent damage from lost, broken-off tines

**FEL152584**

TWISTER 431 DN  
TWISTER 601 DN



### Set of running wheels 340/55-16

**FEL48467804**

TWISTER 11008 T  
TWISTER 13010 T



### Spare wheel with support (16/6.50-8 10 PR)

**FEL49957104**

TWISTER 5204 DN  
TWISTER 6606 DN  
TWISTER 7706 DN  
TWISTER 8608 DN  
TWISTER 901 T



#### Set of running wheels 380/55-17

**FEL42988604**


FORMER 7850



#### Contact wheel (15/6.00-6)

- Optionally available spring-centred creeper wheel (upper link is in a hanging mounting link on the 3 point hitch)
- Contact wheel always sets down on ground in direction of travel
- Tractor 3-point hydraulics can be driven in floating position
- Contact wheel takes over the guiding of the machine over the contours of the ground
- Tedder is guided independently of the tractor

**FEL48464701**



FORMER 351 DS  
FORMER 351 DN  
FORMER 391 DN  
FORMER 426 DN  
FORMER 456 DN



### Universal gear

Made of aluminium alloy casting for the front insert of the machine, suitable for front power take-off

- 540 rev/min anti-clockwise
- 1000 rev/min anti-clockwise and clockwise
- Not necessary with front power take-off 540 rev/min clockwise

**FEL499563**

FORMER 351 DS



### Front mounting kit

Front installation for

- Better overview of the machine
- Maximum protection of the forage, because mowings no longer driven over by the tractor
- Consisting of: contact wheel, relieving spring and all-round protection



**FEL49956401**

FORMER 351 DS



#### 1 Set of tandem axle with wheel (16/6.50-8)

Tandem axle ensures

- Best adjustment to the ground even on uneven ground
- Quiet running even at high driving speeds

\* 2 sets necessary




**FEL49956501**

FORMER 351 DN  
FORMER 391 DN  
FORMER 426 DN  
FORMER 1603\*  
FORMER 801\*  
FORMER 880\*  
FORMER 12545\*

**FEL49956604**

FORMER 1402 \*  
FORMER 1452\*  
FORMER 671\*



#### Individual lifting for the rotors

One-sided lifting of the rotors


- Each can be lifted out separately using a SAV control unit
- In total 2 SAV control units are necessary on the tractor
- Possible to cleanly swath inaccessible places such as field edges and corners




**FEL499567**

FORMER 671  
FORMER 801  
FORMER 880  
FORMER 8055 PRO



	<b>Warning plates</b>
<b>FEL161555</b>	FORMER 351 DS FORMER 351 DN FORMER 391 DN FORMER 426 DN FORMER 456 DN

	<b>Electric lighting</b>
<b>FEL161556</b>	FORMER 351 DS FORMER 351 DN FORMER 391 DN FORMER 426 DN FORMER 456 DN



#### Additional swath former

- Enables the formation of 2 individual swaths
- To be recommended with large quantities of forage



**FEL49956804**

FORMER 1402  
FORMER 1452  
FORMER 1603  
FORMER 7850  
FORMER 7850 PRO



Option 1:

#### Spare wheel with support (16/6.50-8 10 PR)



Option 2:

**FEL49957104**

FORMER 351 DN  
FORMER 391 DN  
FORMER 426 DN  
FORMER 456 DN  
FORMER 1402  
FORMER 1452  
FORMER 1603  
FORMER 7850  
FORMER 7850 PRO  
FORMER 671  
FORMER 801  
FORMER 880  
FORMER 12545  
FORMER 12545 PRO  
FORMER 14055 PRO






### Electrohydraulic individual lift (preselect switching)

**FEL49957804**

FORMER 14055 PRO




### 5th tine conversion kit

- Only for the rear rotor

**FEL499577**

FORMER 12545  
FORMER 12545 PRO



### Electrohydraulic individual lift (preselect switching)

- Single lift of the rotors conveniently possible from the tractor cab
- Preselect switching using toggle switch
- No further control unit required
- Power supply with 2-pin Cobo plug



**FEL167861**

FORMER 671  
FORMER 801  
FORMER 880  
FORMER 8055 PRO



#### CH signage kit

**FEL16954409**

FORMER 1402  
FORMER 1452  
FORMER 1603  
FORMER 7850  
FORMER 7850 PRO  
FORMER 671  
FORMER 801  
FORMER 880  
FORMER 8055 PRO  
FORMER 10065 PRO  
FORMER 12545  
FORMER 12545 PRO  
FORMER 14055 PRO



#### Hydraulic set swath former

- Retrofitting not possible before model year 2018
- For rear use only

**FEL499591**

FORMER 351 DS  
FORMER 351 DN  
FORMER 391 DN  
FORMER 426 DN  
FORMER 456 DN



# FENDT

## Leaders drive Fendt.



**GENUINE  
ACCESSORIES**



© AGCO 2018. AGCO Parts provides worldwide genuine support to all AGCO machinery brands. EN2962.18

Every effort has been made to ensure that the information contained in this publication is as accurate and current as possible. However inaccuracies, errors or omissions may occur and applicability data may be changed at anytime without notice. Therefore, applications should be confirmed prior to any purchase. Images for illustrative purposes only.