

Warning and Hazard Lighting



LED Class I Beacon
GR77873

LED Class I Beacon

- Eight 3-watt LEDs provide unrivaled flash intensity
- Double (80) or quad (65) flash operation with hi/lo intensity control
- Designed for vibration resistance and heat dispersion
- Die-cast aluminum base is coated against corrosion
- Thread-on polycarbonate lens allows for easy "no-tool" pattern selection
- Reverse-polarity, voltage-spike and surge-protected
- 12V to 24V operation spread

Part Number: GR77873

49322 Color of Lamp

Material: Aluminum/Polycarbonate

FMVSS: SAE: J845

Color: Yellow

Class: I

Voltage Amp: 12V - 24V / 3.7A

Pack Quantity: 1



Flexible-Base Strobe Lamp
GR76963

Flexible-Base Strobe Lamp

- DIN fixing allows product to be quickly installed or moved with use of mounting stems
- 75 flashes per minute (double flash), 7 joules
- Flexible rubber stem allows for 30° angle deflection
- Shock-absorbing features make this lamp suitable in rugged applications, such as on forestry, agricultural and industrial vehicles
- Robust polycarbonate thread-on lens is secured with a single set-screw
- Corrosion-resistant materials
- Mounting stems ordered separately

Part Number: GR76963

76963 Yellow

Class: II

Material: Polycarbonate

Finish: Yellow

Voltage Amp: 12 to 48V (DC) - 1.5 AMP

Mounting Stem 43665

Pack Quantity: 1



Stealth Strobe Light
GR76493

Stealth Low-Profile Strobe Light

- Durable belt drive rotator
- 160 flashes per minute
- Thread-on lens is secured quickly with a single screw
- Quick-connect base allows for easy installation and removal

Part Number: GR76493

76493 Yellow

Class: I

SAE: J845

Volts / Amps: 12V - 5.2 AMP

Replacement Bulb: H1, 55 watt

Mounting Stem: 43665

Pack Quantity: 1



© 2015 AGCO Corporation. AGCO and the AGCO logo are registered trademarks of AGCO Corporation. 15007_S1

Contact your FPM or Inside Sales Representative for more information



Warning and Hazard Lighting



LED Warning Light
GR77923

Directional, Portable, Battery-Operated LED Warning Light

- Push button operation
- 72 hours of operation on two AA batteries (not included)
- Includes a magnetic base and is adjustable 180°
- Additional reflective lens as added safety feature
- 3 user-selectable flash patterns

Part Number: GR77923

77923 Yellow

Material: Nylon/Polycarbonate

Finish: Red/Yellow

Pack Quantity: 4



Lightbar
GR76983

Lightbar

- Low profile provides high performance characteristics of LED lighting in a small size
- 6 internal LED modules provide 360° light output
- Built-in electronic flasher with 46 Scan-Lock™ flash patterns (30 for 76770, 76983, 76993) plus 4 simulated rotating patterns (permanent-mount version only)
- Permanent mount includes 6" pigtail; magnetic mount includes 8' straight cord with accessory plug that includes LED indicator switch
- Permanent mount on 14 1/16" x 3 7/16" hole centers
- Mounting hardware and instructions included

Part Number: GR76983

Pack Quantity: 1



© 2015 AGCO Corporation. AGCO and the AGCO logo are registered trademarks of AGCO Corporation. 15007_S2

Contact your FPM or Inside Sales
Representative for more information

